

## ATLANTIS COMPRESSOR OIL

68, 100, 150

IS: 13256-1992 (RA 2004) TYPE DAA, DIN 51506 VD-L

### Product Data Sheet

**PRODUCT DISCRIPTION:** ATLANTIS COMPRESSOR OIL grades are manufactured from highly refined base stock with oxidation, rust, corrosion and foam inhibitors. They provide excellent lubrication under high temperature and high load conditions with low carbon-forming tendency and protection against entrained air. ATLANTIS COMPRESSOR grades are designed to provide superior thermal and oxidation stability and rust protection.

**APPLICATION:** ATLANTIS COMPRESSOR OIL are recommended for use in the cylinder lubrication of reciprocating and rotary air compressors operating up to 220<sup>o</sup>C air discharge temperature.

**PERFORMANCE LEVEL:** Meets IS 13256 – 1992 (RA 2004) TYPE DAA, DIN 51506 VD-L

### Typical Properties

CHARACTERISTICS	ATLANTIS COMPRESSOR OIL		
	68	100	150
Grades	68	100	150
Kinematic Viscosity @40 <sup>o</sup> C, cSt.	66-70	95-105	145-160
Viscosity Index, Min.	100	100	100
Flash Point, COC, <sup>o</sup> C,Min.	230	230	240
Pour Point, <sup>o</sup> C, Max.	(-)12	(-)9	(-)9
Copper Strip Corrosion for 3 hrs @ 100 <sup>o</sup> C	1	1	1
Emulsion Characteristics, Max	40-40-0(10)	40-40-0(10)	40-40-0(10)
Rust Preventing Characteristics	Passes	Passes	Passes

These are typical figures and do not constitute specification. In pursuit of continuous improvement, these figures may be changed without notice at sole discretion of Aryan Lubricants Pvt. Ltd.